

Dolomite dust clogging test equipment

Description:

The equipment comprises the chamber, as described in the standards, together with an automatic dust dispenser and air mover to draw air through the chamber.

Also included are an electronic dust deposition indicator, digital manometer and USB data logger.

The sample is supported in the dust stream by means of a suitable fixture.



Services required:

Floor mounted 110/230 volts AC, 50/60Hz, mains electricity Instrument quality compressed air 100mm diameter exhaust ducting to outside of the building. Anemometer Computer

Approximate packed size & weight:

To be advised with quotation

Relevant standards:

EN 143 (as supplied)

EN 149 (requires additional breathing machine & humidifier)

EN 405 (as supplied)

EN 1827 (requires additional breathing machine & humidifier)

EN 12941 (requires additional breathing machine & Sheffield Headform)

EN 12942 (requires additional breathing machine & Sheffield Headform)

EN 13274-8 (requires additional breathing machine & humidifier for some methods)

EN 14387 (as supplied)



理寶科技有限公司 Libero Techonology Company Limited

香港 Hong Kong 上海 Shanghai 廣州 Guangzhou

www.liberohk.com

T: (852) 2555 8222 T: 86 (21) 5655 8285 T: 86 (20) 3928 3292 Email: sales@liberohk.com