

Strip Printer L 5130 MINIPRINT



SCOPE AND FUNCTION

The Strip Printer L 5130 MINIPRINT is used for automatic documentation of the test results of various TEXTEST-instruments on a 57 mm (2.25") wide paper strip.

HYDROSTATIC HEAD DYNAMIC TEST METHOD ID: Gradi ent: 60 mbar/min 100 cm² Test area: Instrument: FX 3000-III 651 S/n: 20. 1. 2005 Date: 12:07 Time: Operator: 1st / 3rd drop: 1630 1770 mbar 915 2: 918 mbar del eted 1600 1690 mbar 3: 1790 1860 mbar 1773 mbar 1673 Ava: 1600 1690 mbar Mi n: Max: 1790 1860 mbar 4.8

Test report for the Hydrostatic Head Tester FX 3000 HYDROTESTER III (original size).

TECHNICAL SPECIFICATIONS

- Entry data range:
- Length of test series:
- Content of the test report:
- Printer paper:
- Languages:
- Power requirements:
- Dimensions (w x d x h):

The printer is supplied complete with a 1.8 m (6 ft) long data cable, 10 rolls of printing paper and a set of brackets

During testing, the printer continuously prints the individual test results. The test report is automatically complemented by the test parameters, the instrument, date and time plus a statistical analysis of the test results. The test specimen ID and the operator can be manually added.

Thus, the printer provides for reliable and complete documentation of the test results and relives the operator of all time consuming and error-prone reading, writing and calculating tasks. The printer is equally suited for instruments in a laboratory environment and for instruments located directly in the production area.

The Strip Printer L 5130 MINIPRINT can be connected to the following TEXTEST-instruments:

- FX 3000 Hydrostatic Head Tester I, II and HYDROTESTER III
- FX 3250 Automatic Pick Counter PICK-COUNTER
- FX 3300 Air Permeability Tester I, II and LABOTESTER III
- FX 3310 Air Permeability Tester with pneumatic sample clamp
- FX 3350 Dynamic Air Permeability Tester AIRBAG-TESTER
- FX 3700 Digital Tearing Tester
- FX 3750 Digital Tearing Tester ELMENDORF-TESTER.

The printer handles five languages: English, German, French, Italian and Spanish.

+ 0.0001 through + 999,999

1 through 999 tests

Header: Test parameters, instrument, date and time. The test specimen ID and the operator can be manually added.

Individual test results

Trailer: Average, minimum and maximum test result, coefficient of variation CV.

Thermo paper, 57 mm (2.25") wide.

English, German, French, Italian and Spanish. 100 through 240 V, 50 through 60 Hz, 10 W.

30 x 13 x 9 cm.

to mount the printer on the FX 3300 Air Permeability Tester.

ACCESSORY

L 5130-PAP Printing paper

Thermo paper 57 mm (2.25") x 40 m.

Box of 10 rolls.



理寶科技有限公司 Libero Technology Limited

Web Site: http://www.liberohk.com Email: sales@liberohk.com