PORTACOUNT® PRO+ RESPIRATOR FIT TESTER MODEL 8038

RESPIRATOR FIT TESTING YOU CAN TRUST

No other fit tester can quantitatively fit test all types of respirators– gas masks, SCBAs, respirators, even N95, P1 and P2 disposable (filtering-facepiece) respirators. The PortaCount® Pro+ Model 8038 Respirator Fit Tester eliminates the guesswork associated with tedious and error-prone qualitative fit test methods. If the mask requires fit testing, count on the PortaCount Pro+ fit tester to provide the fastest, easiest and best HSE and OSHA-accepted fit test method.

PortaCount Pro+ Respirator Fit Tester Kit Includes

- + Carrying case
- + AC adapter
- + Alcohol supply (enough for ~240 hours of operation)
- + FitPro+[™] Fit Test Software on CD
- + USB computer interface cable
- + Particle Generator (shipped separately)
- + Operation and service manual

For additional software information, see the TSI FitPro+ Fit Test Software Specification Sheet.

Features and Benefits

- + Greater simplicity with the built-in N95-Companion[™] technology
- + Stand-alone operation-no external computer required
- + Reduces need for an external particle generator
 - Redesigned DMA for enhanced performance
 - Ability to perform N95, P2 and P1 fit testing with much lower ambient particle concentrations
- + Color touch screen
- + HSE and OSHA-compliant for all respirators, including N95, P1 and P2
- + Measures fit factors greater than 10,000
- + Switch between different respirator types in under a minute
- + Automates fit testing with FitPro+ Fit Test software
- + Software prints fit test cards with fit test report or on ID cards



UNDERSTANDING, ACCELERATED

SPECIFICATIONS

PORTACOUNT® PRO+ RESPIRATOR FIT TESTER MODEL 8038

Fit Factor Range

1 to greater than 10,000, 1 to 200 for N95 masks

Respirator Facepieces that can be Fit Tested

Full-face elastomeric Half-face elastomeric NIOSH series-100 filtering-facepiece NIOSH series-99 filtering-facepiece P3 filtering-facepiece P2 filtering-facepiece P1 filtering-facepiece

Fit Factor Measurement Direct measurement of fit factor $(C_{out}/C_{in})^*$

Dimensions

6.75 in. x 8.5 in. x 9.5 in. (17 cm x 22 cm x 24 cm)

Weight Unit Only With Standard Accessories and Case

Power Autosensing 100 to 250 VAC, 50 to 60 Hz

Flow Rate Sample Total

350 cm³/min 1000 cm³/min (nominal)

6.8 lb. (3.1 kg)

18 lb. (8.2 kg)

Temperature Range

Operation Storage

Alcohol Hours Per Charge Alcohol Type

Carrying Case Dimensions (HWD) 32 to 100°F (0 to 38°C) -40 to 122°F (-40 to 50°C)

6 hours at 70°F (21°C) 99.5%+ reagent grade isopropyl

9 in. x 13.7 in. x 19.5 in. (23 cm x 34.8 cm x 49.5 cm)

Pass/Fail Setting

User-selectable: 0 to 10,000

Factory Recalibration Interval One year

Warranty

Two years on workmanship and materials

Minimum PC Hardware Requirements for FitPro+ Fit Test Software

Windows® 7 (32 and 64 bit), Windows 8 (32 and 64 bit), or Windows 10 (32 and 64 bit) operating system Microsoft.Net version 4 (installation software will install Microsoft.Net if necessary) Note – An internet connection is required to install Microsoft.Net ≥ 1 GHz process ≥ 1280 x 800 screen resolution monitor 500 MB free space on hard drive 1 free USB port CD-ROM reader or internet connection (to install the software)

Optional Accessories

Mask Sampling Adapters for select respirator models

 $^{\star}\mbox{Mask}$ leakage is measured simultaneously while test subject moves and breathes.

PortaCount, TSI, and the TSI logo are registered trademarks, and FitPro+, and N95-Companion are trademarks of TSI Incorporated.

Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries.

To see our list of patents please visit: www.tsi.com/patents





試

測

Testing Equipmen

理寶科技有限公司 Libero Techonology Company Limited

香港 Hong Kong 上海 Shanghai 廣州 Guangzhou www.liberohk.com T: (852) 2555 8222 T: 86 (21) 5655 8285 T: 86 (20) 3928 3292 Email: sales@liberohk.com